

SAFETY DATA SHEET

PRODUCT NAME KEM AQUA Solvent FAT

Data of issue

6/11/2018

Date of revision/
Last confirmation

10/9/2024

1. Identification of the substance or mixture and the supplier

Product name KEM AQUA Solvent FAT

SDS No. GHS-0067E

Name of supplier Kyoto Electronics Manufacturing Co., Ltd.

Address 68 Ninodan-cho, Shinden, Kisshoin, Minami-ku, Kyoto, Japan

Division Quality Assurance Department

Phone +81-75-691-4121 Fax +81-75-691-4127

Recommended uses and restrictions on use

Recommended use For analysis

Restrictions on use When using for purposes other than those recommended, consult a specialist.

2. Hazard identification

GHS classification

Physical hazards

Flammable liquids Category 3

Health hazards

Acute toxicity / Oral Category 4

Acute toxicity / Inhalation Category 4

Skin corrosion / Irritation Category 2

Serious eye damage / Eye irritation Category 1

Germ cell mutagenicity Category 2

Carcinogenicity Category 2

Reproductive toxicity Category 1B

Specific target organ toxicity (single exposure) Category 1(Liver, Respiratory organs, Kidney, Systemic

toxicity, Central nervous system, Cardio-vascular

system, Visual organs)

Category 3(Narcotic effects)

Specific target organ toxicity (repeated exposure Category 1(Liver, Respiratory organs, Kidney, Central

nervous system, Visual organs)

Environmental hazards



Short-term (acute) aquatic hazard

Long-term (chronic) aquatic hazard

Long-term (omonio) aquatic

Category 3
Category 1

GHS label elements

Hazard pictograms



Signal words

Hazard statements

Danger

H226 Flammable liquid and vapor.

H302 + H332 Harmful if swallowed or if inhaled.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H336 May cause drowsiness or dizziness.

H341 Suspected of causing genetic defects.

H351 Suspected of causing cancer.

H360 May damage fertility or the unborn child.

H370 Causes damage to organs (Liver, Respiratory organs, Kidney, Systemic toxicity, Central nervous system, Cardio-vascular system).

H372 Causes damage to organs (Liver, Respiratory organs, Kidney, Central nervous system) through prolonged or repeated exposure.

H402 Harmful to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

Precautionary statement

Prevention

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have

been read and understood.

P210 Keep away from heat, hot surfaces, sparks, open

flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving

equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting/

equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.



Response

P260 Do not breathe mist or vapors.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this

product.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye

protection/ face protection.

P301 + P312 + P330 IF SWALLOWED: Call a POISON

CENTER/ doctor if you feel unwell. Rinse mouth.

P303 + P361 + P353 IF ON SKIN (or hair): Take off

immediately all contaminated clothing. Rinse skin with

water.

P304 + P340 + P312 IF INHALED: Remove person to

fresh air and keep comfortable for breathing. Call a

POISON CENTER/ doctor if you feel unwell.

P305 + P351 + P338 + P310 IF IN EYES: Rinse

cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue

rinsing. Immediately call a POISON CENTER/ doctor.

P308 + P311 IF exposed or concerned: Call a POISON

CENTER/ doctor.

P332 + P313 If skin irritation occurs: Get medical advice/

attention.

P362 + P364 Take off contaminated clothing and wash it

before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical

or alcohol-resistant foam to extinguish.

P391 Collect spillage.

Storage P403 + P233 Store in a well-ventilated place. Keep

container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal P501 Dispose of contents/ container to an approved

waste disposal plant.

Other hazards which do not result in classification

None known.



3. Composition/Information on ingredients

substance / mixture mixture

Components

No.	Chemical name	CAS No.	Concentration	ENCS / ISHL
			(% w/w)	number
1	chloroform	67-66-3	>=80-<90	2-37
2	methanol	67-56-1	10-20	2-201
3	2-(methylamino)pyridine	4597-87-9	1-5	8-(1)-3318
4	sulfur dioxide	7446-09-5	<1	1-536
5	ethanol	64-17-5	<1	2-202

4. First-aid measures

General advice Move out of dangerous area.

Consult a physician.

Show this material safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Call a POISON CENTER or doctor/physician if you feel unwell.

In case of skin contact Wash off with soap and plenty of water.

Wash contaminated clothing before re-use. Remove contaminated clothing and shoes.

If skin irritation or rash occurs: Get medical advice/ attention.

In case of eye contact Immediately flush eye(s) with plenty of water.

Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

Remove contact lenses, if present and easy to do. Continue rinsing.

If swallowed Rinse mouth with water.

Do NOT induce vomiting.

If large quantities of this material are swallowed, call a physician immediately.

Most important symptoms Harmful if swallowed or if inhaled.

and effects, both acute and Causes skin irritation.

delayed Causes serious eye damage.

May cause drowsiness or dizziness.

Suspected of causing genetic defects.

Suspected of causing cancer.



May damage fertility or the unborn child.

Causes damage to organs.

Causes damage to organs through prolonged or repeated exposure.

5. Fire-fighting measures

Suitable extinguishing media Carbon dioxide (CO₂)

Dry sand

Regular foam

Vermiculite

Unsuitable extinguishing media

High volume water jet

Specific hazards during fire

Do not allow run-off from fire fighting to enter drains or water courses.

fighting

Specific extinguishing methods Collect contaminated fire extinguishing water separately. This must not be

discharged into drains.

Fire residues and contaminated fire extinguishing water must be disposed of in

accordance with local regulations.

Use personal protective equipment.

Special protective equipment for

opeoidi protective equipment foi

fire-fighters

6. Accidental release measures

Personal precautions, Use personal protective equipment.

protective equipment and Remo

Remove all sources of ignition.

emergency procedures

Environmental precautions Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal

containment and cleaning up binder, sawdust).

Keep in suitable, closed containers for disposal.

7. Handling and storage

Handling



Advice on protection against fire and Do not spray on a naked flame or any incandescent material.

explosion Take necessary action to avoid static electricity discharge (which might

cause ignition of organic vapors).

Keep away from open flames, hot surfaces and sources of ignition.

Advice on safe handling Take precautionary measures against static discharges.

Keep away from fire, sparks and heated surfaces.

Wash skin thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only in area provided with appropriate exhaust ventilation.

Avoidance of contact No data available

Hygiene measures When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

Storage

Conditions for safe storage Keep in a well-ventilated place.

Store at room temperature.

To maintain product quality, do not store in heat or direct sunlight.

Keep container tightly closed.

Further information on storage

stability

No decomposition if stored and applied as directed.

8. Exposure controls/Personal protection

Threshold limit value and permissible exposure limits for each component in the work environment

Components	CAS-No.	Value type	Control parameters /	Basis	
		(Form of	Reference concentration /		
		exposure)	Permissible concentration		
chloroform	67-66-3	ACL	3 ppm	JP OEL ISHL	
		OEL-M	3 ppm	JP OEL	
			14.7 mg/m ³	JSOH	
	Further information: Skin absorption, Group 2B: possibly carcinogenic to humans				
		TWA	10 ppm	ACGIH	
methanol	67-56-1	ACL	200 ppm	JP OEL ISHL	
		OEL-M	200 ppm	JP OEL	
			260 mg/m ³	JSOH	
	Further information: Group 2: Substances presumed to cause reproductive toxicity in				
	humans, Skin absorption				
		TWA	200 ppm	ACGIH	



		STEL	250 ppm	ACGIH
sulphur dioxide	7446-09-5	STEL	0.25 ppm	ACGIH
ethanol	64-17-5	STEL	1,000 ppm	ACGIH

Biological occupational exposure limits

Components	CAS-No.	Target	Biological	Sampling time	Permissible	Basis
		substance	specimen		concentration	
methanol	67-56-1	Methanol	Urine	End of shift	20 mg/L	JSOH
		Methanol	Urine	End of shift (As	15 mg/L	ACGIH
				soon as		BEI
				possible after		
				exposure		
				ceases)		

Personal protective equipment

Respiratory protection Suitable respiratory equipment

Hand protection material Protective gloves

Eye protection Safety glasses

Skin and body protection Protective suit

9. Physical and chemical properties

Physical state Liquid.

Color Light yellow, transparent

Odor pungent

Melting point / Freezing point No data available
Initial boiling point and boiling range No data available
Flammability (liquids) No data available

Lower explosion limit and upper explosion limit / flammability limit

Upper explosion limit / Upper flammability limit No data available Lower explosion limit / Lower flammability limit No data available

Flash point 51.8 ℃

Decomposition temperature

PH

No data available

No data available

Autoignition temperature

No data available

Self-Accelerating decomposition temperature

No data available

(SADT) Viscosity

Viscosity, kinematic 0.51 mm²/s

Solubility(ies)



Water solubility

Partition coefficient: n-octanol/water

Vapor pressure

Density and / or relative density Relative density

Density

No data available

1.277 (20 ℃)

No data available

Relative vapor density

No data available

Particle characteristics Particle size No data available

10. Stability and reactivity

Reactivity No decomposition if stored and applied as directed.

Chemical stability Stable under normal conditions.

Possibility of hazardous reactions May cause fire, explosion, and/or generation of a hazardous gas

Conditions to avoid No data available

Incompatible materials No data available

11. Toxicological information

Acute toxicity Harmful if swallowed or if inhaled.

Product

Acute oral toxicity

The component/mixture is moderately toxic after single ingestion.

Acute inhalation toxicity Test atmosphere vapor

The component/mixture is moderately toxic after short term inhalation.

chloroform

Acute oral toxicity LD50 (Rat) 440mg/kg

The component/mixture is moderately toxic after single ingestion.

Acute inhalation toxicity LC50 (Rat) 9,770ppm, Exposure time 4 h, Test atmosphere vapor

Test atmosphere vapor

The component/mixture is moderately toxic after short term inhalation.

Acute dermal toxicity LD0 (Rabbit) 3,980 mg/kg

methanol

Acute oral toxicity LD50 1,400 mg/kg

Acute inhalation toxicity LC50 (Rat) 64,000 ppm, Exposure time 4 h, Test atmosphere vapor

LC50 (Rat) 145,000 ppm, Exposure time 1 h, Test atmosphere dust / mist

Acute dermal toxicity LDLo 393mg/kg

sulphur dioxide

Acute inhalation toxicity LC50 (Rat) 593 – 1319 ppm, Exposure time 4 h, Test atmosphere gas

ethanol



Acute oral toxicity LD50 (Rat) 15,010 mg/kg

Acute inhalation toxicity LC50 (Rat) 124.7 mg/L, Exposure time 4 h, Test atmosphere vapor

Acute dermal toxicity LDLo (Rabbit) 20,000 mg/kg

Skin corrosion/irritation Causes skin irritation.

Product Skin irritation

Extremely corrosive and destructive to tissue.

chloroform Skin irritation
2-(methylamino)pyridine Skin irritation

Serious eye damage/eye irritation Causes serious eye irritation.

Product Irreversible effects on the eye

May cause irreversible eye damage.

chloroform Causes serious eye damage.

methanol Causes eye irritation.

2-(methylamino)pyridine Eye irritation.

sulphur dioxide Causes serious eye irritation. ethanol Causes serious eye irritation.

Respiratory or skin sensitization

Skin sensitization Not classified based on available information.

Respiratory sensitization Not classified based on available information.

Germ cell mutagenicity Suspected of causing genetic defects.

Product Suspected of inducing heritable mutations in the germ cells of humans.

chloroform Suspected of inducing heritable mutations in the germ cells of humans.

Carcinogenicity Suspected of causing cancer.

Product Suspected human carcinogens
chloroform Suspected human carcinogens

Reproductive toxicity

Product

Presumed human reproductive toxicant

chloroform

Presumed human reproductive toxicant

methanol

Presumed human reproductive toxicant

Presumed human reproductive toxicant

STOT-single exposure May cause drowsiness or dizziness.

Causes damage to organs (Liver, Respiratory organs, Kidney, Systemic

toxicity, Central nervous system, Cardio-vascular system).

Product Target Organs Liver, Respiratory organs, Kidney, Systemic toxicity, Central

nervous system, Cardio-vascular system, Visual organs

The substance or mixture is classified as specific target organ toxicant, single

exposure, category 1.

The substance or mixture is classified as specific target organ toxicant, single

exposure, category 3 with narcotic effects.



chloroform Target Organs Liver, Respiratory organs, Kidney, Cardio-vascular system

The substance or mixture is classified as specific target organ toxicant, single

exposure, category 1.

The substance or mixture is classified as specific target organ toxicant, single

exposure, category 3 with narcotic effects.

methanol Target Organs Systemic toxicity, Central nervous system, Visual organs

The substance or mixture is classified as specific target organ toxicant, single

exposure, category 1.

The substance or mixture is classified as specific target organ toxicant, single

exposure, category 3 with narcotic effects.

sulphur dioxide Target Organs Respiratory organs

The substance or mixture is classified as specific target organ toxicant, single

exposure, category 1.

ethanol The substance or mixture is classified as specific target organ toxicant, single

exposure, category 3 with respiratory tract irritation.

The substance or mixture is classified as specific target organ toxicant, single

exposure, category 3 with narcotic effects.

STOT-repeated exposure Causes damage to organs (Liver, Respiratory organs, Kidney, Central nervous

system) through prolonged or repeated exposure.

chloroform Target Organs Liver, Respiratory organs, Kidney, Central nervous system

The substance or mixture is classified as specific target organ toxicant,

repeated exposure, category 1.

methanol Target Organs Central nervous system, Visual organs

The substance or mixture is classified as specific target organ toxicant,

repeated exposure, category 1.

sulphur dioxide Target Organs Respiratory organs

The substance or mixture is classified as specific target organ toxicant,

repeated exposure, category 1.

Aspiration toxicity Not classified based on available information.

Remarks Symptoms of overexposure may be headache, dizziness, tiredness,

nausea and vomiting.

Concentrations substantially above the TLV value may cause narcotic

effects.

Solvents may degrease the skin.

12. Ecological information

Ecotoxicity



Product

Acute aquatic toxicity Harmful to aquatic life.

Chronic aquatic toxicity Very toxic to aquatic life with long lasting effects.

chloroform

Toxicity to algae/aquatic EC50 (Chlamydomonas reinhardtii (green algae)) 13.3 mg/L, Exposure time 72 h

plants

Toxicity to fish (Chronic NOEC (Oncorhynchus mykiss (rainbow trout)) 0.059 mg/L, Exposure time 28 Days

toxicity)

M-Factor (Chronic aquatic 1

toxicity) methanol

Toxicity to fish

LC50 (Lepomis macrochirus (Bluegill sunfish)) 15,400 mg/L, Exposure time 96 h

Toxicity to daphnia and EC50 (Daphnia magna (Water flea)) > 10,000 mg/L, Exposure time 48 h

other aquatic invertebrates

Toxicity to algae/aquatic EC50 (Chaetoceros calcitrans) > 10,000 - < 20,000 mg/L, Exposure time 96 h

NOEC (Skeletonema costatum (marine diatom)) 1,400 mg/L, End point Growth plants

inhibition Exposure time 96 h

NOEC (Oreochromis mossambicus) 23.75 mg/L, End point Growth inhibition Toxicity to fish (Chronic

toxicity) Exposure time 90 Days

ethanol

LC50 (Oncorhynchus mykiss (rainbow trout)) 13,000 mg/L, Exposure time Toxicity to fish

Toxicity to daphnia and EC50 (Daphnia magna (Water flea)) 12,340 mg/L, End point mortality, Exposure

other aquatic invertebrates time 48 h

Toxicity to algae/aquatic EC50 (Lemna minor (duckweed)) 3,690 mg/L, End point Growth inhibition,

plants Exposure time 7 Days

NOEC (Lemna gibba (gibbous duckweed)) 280 mg/L, End point Growth inhibition

Exposure time 7 Days

Toxicity to fish (Chronic NOEC (Ceriodaphnia dubia (Water flea)) 9.6 mg/L, End point Reproductive

inhibition, Exposure time 10 Days toxicity)

Persistence and degradability

Biodegradability

chloroform Biochemical oxygen demand Not rapidly biodegradable, Biodegradation 0%,

Exposure time 14 d

methanol Biochemical oxygen demand rapidly biodegradable, Biodegradation 92 %,

Exposure time 14 d

ethanol Biochemical oxygen demand rapidly biodegradable, Biodegradation 89 %

Bioaccumulative potential

Bioaccumulation



chloroform Partition coefficient: n-octanol/water log Pow = 1.97

methanol Species Cyprinus carpio (Carp), Bioconcentration factor (BCF) < 10, Exposure

time: 72 h

Partition coefficient: n-octanol/water log Pow = - 0.77

ethanol Partition coefficient: n-octanol/water $\log Pow = -0.31 (25^{\circ}C)$

Mobility in soil No data available
Hazardous to the ozone Not applicable

layer

or disposal. Harmful to aquatic life. Very toxic to aquatic life with long lasting effects.

13. Disposal considerations

Waste from Can be incinerated, when in compliance with local regulations.

residues Send to a licensed waste management company.

Contaminated Empty remaining contents.

packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Dispose of contents/ container to an approved waste disposal plant.

14. Transport information

International Regulations

IATA-DGR

UN / ID No. UN1993

Proper shipping name Flammable liquid, n.o.s. (Methanol, solution)

Class 3
Packing group III

Labels Flammable Liquids

Packing instruction (cargo aircraft) 366

IMDG-Code

UN No. UN1993

Proper shipping name FLAMMABLE LIQUID, N.O.S. (METHANOL solution)

Class 3
Packing group III
Labels 3

EmS Code F-E, S-E

Marine pollutant no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code



Not applicable for product as supplied.

Domestic regulation

Special precautions for user

Please refer to the law and local regulations, etc. in each country
The transport classification(s) provided herein are for informational
purposes only, and solely based upon the properties of the unpackaged
material as it is described within this Safety Data Sheet. Transportation
classifications may vary by mode of transportation, package sizes, and
variations in regional or country regulations.

15. Regulatory information

16. Other information

Citations/References

NITE-Gmiccs (National Institute of Technology and Evaluation)

NITE-CHRIP (National Institute of Technology and Evaluation)

Workplace Safety Site (Ministry of Health, Labor and Welfare)

SDS from various upstream manufacturers

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.