

# SAFETY DATA SHEET

PRODUCT NAME	<b>KEM AQUA Water-Methanol 2</b>	Date of issue	6/11/2018
		Date of revision/ Last confirmation	10/9/2024

## 1. Identification of the substance or mixture and the supplier

Product name	KEM AQUA Water-Methanol 2
SDS No.	GHS-0075E
Name of supplier	Kyoto Electronics Manufacturing Co., Ltd.
Address	68 Ninodan-cho, Shinden, Kisshoin, Minami-ku, Kyoto, Japan
Division	Quality Assurance Department
Phone	+81-75-691-4121
Fax	+81-75-691-4127
Recommended uses and restrictions on use	
Recommended use	For analysis
Restrictions on use	When using for purposes other than those recommended, consult a specialist.

## 2. Hazard identification

GHS classification

Physical hazards

Flammable liquids	Category 2
-------------------	------------

Health hazards

Acute toxicity / Oral	Category 4
Serious eye damage / Eye irritation	Category 2B
Reproductive toxicity	Category 1B
Specific target organ toxicity (single exposure)	Category 1(Central nervous system, Visual organs, Systemic toxicity)
	Category 3(Narcotic system)
Specific target organ toxicity (repeated exposure)	Category 1(Central nervous system, Visual organs)

GHS label elements

Hazard pictograms



Signal words

## Hazard statements

H225 Highly flammable liquid and vapor.  
H302 Harmful if swallowed.  
H320 Causes eye irritation.  
H336 May cause drowsiness or dizziness.  
H360 May damage fertility or the unborn child.  
H370 Causes damage to organs (Central nervous system, Visual organs, Systemic toxicity).  
H372 Causes damage to organs (Central nervous system, Visual organs) through prolonged or repeated exposure.

## Precautionary statement

## Prevention

P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 Keep container tightly closed.  
P240 Ground and bond container and receiving equipment.  
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.  
P242 Use non-sparking tools.  
P243 Take action to prevent static discharges.  
P260 Do not breathe mist or vapors.  
P264 Wash skin thoroughly after handling.  
P270 Do not eat, drink or smoke when using this product.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

## Response

P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell. Rinse mouth.  
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.  
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with



Most important symptoms and effects, both acute and delayed	<p>Harmful if swallowed.</p> <p>Causes eye irritation.</p> <p>May cause drowsiness or dizziness.</p> <p>May damage fertility or the unborn child.</p> <p>Causes damage to organs.</p> <p>Causes damage to organs through prolonged or repeated exposure.</p>
Notes to physician	<p>Treat symptomatically.</p>

## 5. Fire-fighting measures

Suitable extinguishing media	Product is compatible with standard fire-fighting agents.
Unsuitable extinguishing media	High volume water jet
Specific hazards during fire fighting	Do not allow run-off from fire fighting to enter drains or water courses.
Specific extinguishing methods	<p>Collect contaminated fire extinguishing water separately. This must not be discharged into drains.</p> <p>Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.</p>
Special protective equipment for fire-fighters	<p>Use personal protective equipment.</p> <p>Remove all sources of ignition.</p>

## 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	<p>Use personal protective equipment.</p> <p>Remove all sources of ignition.</p>
Environmental precautions	<p>Prevent further leakage or spillage if safe to do so.</p> <p>If the product contaminates rivers and lakes or drains inform respective authorities.</p>
Methods and materials for containment and cleaning up	<p>Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).</p> <p>Keep in suitable, closed containers for disposal.</p> <p>Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).</p>

## 7. Handling and storage

Handling

Advice on protection against fire and explosion	Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Keep away from open flames, hot surfaces and sources of ignition.
Advice on safe handling	Take precautionary measures against static discharges. Keep away from fire, sparks and heated surfaces. Wash skin thoroughly after handling. Do not eat, drink or smoke when using this product. Use only in area provided with appropriate exhaust ventilation.
Avoidance of contact	Strong oxidizing agents
Hygiene measures	When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

Storage

Conditions for safe storage	Keep in a well-ventilated place. Store at room temperature. To maintain product quality, do not store in heat or direct sunlight. Keep container tightly closed.
Further information on storage stability	No decomposition if stored and applied as directed.

## 8. Exposure controls/Personal protection

Threshold limit value and permissible exposure limits for each component in the work environment

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Reference concentration / Permissible concentration	Basis
methanol	67-56-1	ACL	200 ppm	JP OEL ISHL
		OEL-M	200 ppm 260 mg/m <sup>3</sup>	JP OEL JSOH
		Further information: Group 2: Substances presumed to cause reproductive toxicity in humans, Skin absorption		
		TWA	200 ppm	ACGIH
		STEL	250 ppm	ACGIH

Personal protective equipment

Respiratory protection	Suitable respiratory equipment
Hand protection material	Protective gloves
Eye protection	Safety glasses

Skin and body protection      Protective suit

## 9. Physical and chemical properties

Physical state	Liquid.
Color	colorless, transparent
Odor	pungent
Melting point / Freezing point	- 94.8 °C
Initial boiling point and boiling range	64.6 °C
Flammability (liquids)	No data available
Lower explosion limit and upper explosion limit / flammability limit	
Upper explosion limit / Upper flammability limit	36.5 %(V)
Lower explosion limit / Lower flammability limit	6.0 %(V)
Flash point	10.9 °C (Tag closed cup)
Decomposition temperature	No data available
pH	No data available
Autoignition temperature	470.0 °C
Self-Accelerating decomposition temperature (SADT)	No data available
Viscosity	
Viscosity, kinematic	No data available
Solubility(ies)	
Water solubility	completely soluble
Solubility in other solvents	completely soluble (Solvent Esters)
Partition coefficient: n-octanol/water	No data available
Vapor pressure	12.67 mmHg (20 °C)
Density and / or relative density Relative density	0.792 (20 °C)
Density	No data available
Relative vapor density	No data available
Particle characteristics Particle size	No data available

## 10. Stability and reactivity

Reactivity	No decomposition if stored and applied as directed.
Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	No data available
Conditions to avoid	No data available
Incompatible materials	Strong oxidizing agents

Hazardous decomposition products      No data available

## 11. Toxicological information

Acute toxicity	Harmful if swallowed.
methanol	
Acute oral toxicity	LD50 1,400mg/kg
Acute inhalation toxicity	LC50 (Rat) 64,000ppm, Exposure time 4 h, Test atmosphere vapor LC50 (Rat) 145,000ppm, Exposure time 1 h, Test atmosphere dust / mist
Acute dermal toxicity	LDLo 393mg/kg
Skin corrosion/irritation	Not classified based on available information.
Product	May cause skin irritation in susceptible persons.
Serious eye damage / eye irritation	Causes eye irritation.
Product	Vapors may cause irritation to the eyes, respiratory system and the skin.
methanol	Causes eye irritation.
Respiratory or skin sensitization	
Skin sensitization	Not classified based on available information.
Respiratory sensitization	Not classified based on available information.
Germ cell mutagenicity	Not classified based on available information.
Carcinogenicity	Not classified based on available information.
Reproductive toxicity	May damage fertility or the unborn child.
methanol	Presumed human reproductive toxicant
STOT-single exposure	May cause drowsiness or dizziness. Causes damage to organs (Central nervous system, Visual organs, Systemic toxicity).
methanol	Target Organs Systemic toxicity, Central nervous system, Visual organs The substance or mixture is classified as specific target organ toxicant, single exposure, category 1. The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.
STOT-repeated exposure	Causes damage to organs (Central nervous system, Visual organs) through prolonged or repeated exposure.
methanol	Target Organs Central nervous system, Visual organs The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 1.
Aspiration toxicity	Not classified based on available information.
Remarks	Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Concentrations substantially above the TLV value may cause narcotic

effects.

Solvents may degrease the skin.

## 12. Ecological information

### Ecotoxicity

#### methanol

Toxicity to fish LC50 (*Lepomis macrochirus* (Bluegill sunfish)) 15,400 mg/L, Exposure time 96 h

Toxicity to daphnia and other aquatic invertebrates EC50 (*Daphnia magna* (Water flea)) > 10,000 mg/L, Exposure time 48 h

Toxicity to algae/aquatic plants EC50 (*Chaetoceros calcitrans*) > 10,000 - < 20,000 mg/L, Exposure time 96 h  
 NOEC (*Skeletonema costatum* (marine diatom)) 1,400 mg/L, End point Growth inhibition, Exposure time 96 h

Toxicity to fish (Chronic toxicity) NOEC (*Oreochromis mossambicus*) 23.75 mg/L, End point Growth inhibition  
 Exposure time 90 Days

### Persistence and degradability

#### Biodegradability

methanol Biochemical oxygen demand rapidly biodegradable, Biodegradation 92 %, Exposure time 14 d

### Bioaccumulative potential

#### Bioaccumulation

methanol Species *Cyprinus carpio* (Carp), Bioconcentration factor (BCF) < 10, Exposure time: 72 h

Partition coefficient: n-octanol/water log Pow = - 0.77

Mobility in soil No data available

Hazardous to the ozone layer Not applicable

#### Other adverse effects

No data available

## 13. Disposal considerations

Waste from residues Can be incinerated, when in compliance with local regulations.

Send to a licensed waste management company.

Contaminated packaging Empty remaining contents.

Empty containers should be taken to an approved waste handling site for recycling or disposal.

Dispose of contents/ container to an approved waste disposal plant.



## 14. Transport information

### International Regulations

#### IATA-DGR

UN / ID No.	UN1230
Proper shipping name	Methanol (solution)
Class	3
Subsidiary risk	6.1
Packing group	II
Labels	Flammable Liquids, Toxic
Packing instruction (cargo aircraft)	364
Packing instruction (passenger aircraft)	352

#### IMDG-Code

UN No.	UN1230
Proper shipping name	METHANOL (solution)
Class	3
Subsidiary risk	6.1
Packing group	II
Labels	3 (6.1)
EmS Code	F-E, S-D
Marine pollutant	no

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### Domestic regulation

Please refer to the law and local regulations, etc. in each country

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## 15. Regulatory information

## 16. Other information

### Citations/References

NITE-Gmiccs (National Institute of Technology and Evaluation)

NITE-CHRIP (National Institute of Technology and Evaluation)  
Workplace Safety Site (Ministry of Health, Labor and Welfare)  
SDS from various upstream manufacturers

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.